

TECHNICAL DATA

NUIMAGE

Non-Fogging Cleaner & Debugger for Polished Metals

Nulmage is the answer to debugging and oil removal problems for show quality bright work! Nulmage cleans and debugs your outstanding polish job without the fogging of normal cleaners or waxes and will save time and effort while maintaining that famous “Nuvite Look” achieved with Nuvite **NuShine II** metal polishes.

Nulmage works great for cleaning polished skins on grills, bumper guards, bug shields, removing oils and fluids without the “rainbow effect” that are usually left on the surface from oil residue. And, it’s easy, too — apply Nulmage on a soft cotton flannel rag and apply, wetting bug spots, rubbing gently and spreading over the surface until clean. Continue over the surface, and when complete, final buff away the slight, dried haze to reveal the beautiful clear shine!

Nulmage even works great as a final cleanup for black metal polish residue on paint, and will help remove excess polish after power buffing.

Nulmage: the ANSWER to polished metal cleaning & upkeep!

- Debugs and cleans without fogging the depth and image reflection of highly polished metal
- Imparts a chemical barrier against soil redistribution
- Maintains the “Nuvite Look”!
- Conforms to Airframe OEM standards and specifications

PHYSICAL CHARACTERISTICS

- **Appearance:** Off white cream
- **Odor:** Mild
- **pH:** 9.1 – 9.5 @ 25°C
- **Specific Gravity** 1.06 @ 25°C
- **Solubility:** Dispersible
- **Flash Point:** None

INSTRUCTIONS FOR USE

Nuvite Nulmage is intended for use as a cleaner for well-polished metals and paints. Use Nuvite **NuShine II** system of graded metal polishing compounds to polish metals. To clean polished surfaces: pour a small amount of Nulmage onto a soft cotton polishing cloth (cotton flannel), and apply to surface. Wipe on gently to avoid mechanical scratching from surface soils and dust. Spread material over the whole polished area and gently spread, rubbing until Nulmage is removed. A very slight haze will remain. Allow this haze to dry as you continue with the other areas to be cleaned.



85 JETSON LANE, CENTRAL ISLIP, NEW YORK 11722
516.935.4000 FAX 516.935.4039

WWW.NUVITECHEMICAL.COM
WWW.UNIVERSALPHOTONICS.COM

After haze has been allowed to dry completely, polish away to bright shine with a clean cotton flannel polishing cloth. To remove stubborn bugs, apply wet Nulmage on bug spot and continue to spread material on the area around the bug while the wet Nulmage soaks bug material and rub away bug residue, or keep any remaining bug residue wet and soaking so that it can be removed with gentle rubbing. Continue going back over bug spot, rewetting area with Nulmage wetted flannel until gone.

When using Nuvite products, please use recommended procedures and equipment. For further product information, and technical support, consult a Nuvite Representative at 800.394.8351

HEALTH AND SAFETY

Users should use standard safety precautions, such as wearing gloves and eye protection along with any other standard safety procedures. Refer to Safety Data Sheet for further health and safety information.

AVAILABILITY

Nulmage is available in 1 pint, 1, 4 & 8 oz samples, 1 quart, 1, 5, and 55 gallon drums.

This technical data sheet is offered in good faith without warranty or representation solely for the buyer's use in the evaluation of this product. It is the responsibility of the buyer and end user to determine the data and safety information with respect to applicable laws, regulations, and the fitness & character of this product prior to full scale use. UNIVERSAL PHOTONICS and or NUVITE CHEMICAL COMPOUNDS (seller) assumes no legal liability for any injury, accident, loss, or damage through the use of this product of which such uses are beyond seller's control. nulmage.10.16.td